



Product Specification

SC 118-480



Product	434	Tolerance	
Dimensions (I*w in mm)	ø117,8x67,2	± 0,7 mm	
Weight (gr)	16,8	± 2,0 g	
Volume to rim (ml)	545		
Volume under lid (ml)	460		
Material	рр		
Colour	on request		
Closure Type	tamper evident		
Mould number	201805290		
Handle (option)	no		
Handle weight (gr)	-		
IML decoration	on request		

Logistic information

Logistic information		
Packaging type	Box nr. 7 (590x390x334)	
Pallet height (incl. pallet) (cm)	220	
Quantity per packaging type	300	
Quantity per pallet	6,000	
Bruto weight pallet (kg)	185,4	
Pallet type	Europallet (80x120cm)	

Storage conditions

Suitible storage: do not expose to direct sunlight, humidity and frost. Stackability depends on many factors, customers should make internal trials to dertimine the viability of stacking and transportation.

Use

Filling in °C	85
Dishwasher safe	yes
Microwavable	yes
Freezer usage	no
Best before: 12 months after delivery date	
Best processing temperature: minumum 10 °C at least 8 hours before filling	

- * **Hot filling**: the packaging is suitable for hot filling, notably after hot filling the products can be more flexible. This can be have influence on stacking, the packaging must be tested by the customer before approval for use.
- * **Cold temperatures**: Freezing conditions require special resins, available on request. The packaging must be tested by the customer before approval for use.

Miscellaneous

All deliveries are subject to the General Terms and Conditions of Sale of Intopack B.V. (Dutch chamber of commerce no. 16044140). Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that Intopack recommends. All Intopack Products comply with the European Union Commission Regulation No. 10/2011/EU with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. Deviations in the products of 0,025% or less (i.e. 25 items per 100.000) are considered acceptable in the industry and therefore cannot be construed as a defect. The product specification are subject to change without notice.







