

Product Specification

SC95-290

SC 95LID

Copack



Container
SC95-290



Lid
SC 95LID

Product	472-C	Tolerance	423-2	Tolerance
Dimensions (l*w in mm)	94,30 x 64,0	± 0,70 mm	ø93,2 x 6,9	± 0,7 mm
Weight (gr)	10,6	± 0,6 g	5,0	± 0,5 g
Volume to rim (ml)	330		-	
Volume under lid (ml)	290		-	
Material	PP		PP	
Colour	on request		on request	
Closure Type	tamper evident		tamper evident	
Mould number	44708		201704070	
Handle (option)	no		no	
Handle weight (gr)	-		-	
IML decoration	on request		on request	

Logistic information

Quantity per packaging type	400	400
Quantity per pallet	10,000	10,000
Packaging type	Box nr. 7 (590x390x334)	
Pallet type	Europallet (80x120cm)	
Bruto weight pallet (kg)	200,2	
Pallet height (incl. pallet) (cm)	255	

Storage conditions

Suitable storage: do not expose to direct sunlight, humidity and frost. Stackability depends on many factors, customers should make internal trials to determine the viability of stacking and transportation.

Use

Filling in °C	85
Dishwasher safe	yes
Microwavable	yes
Freezer usage	on request
Best before: 12 months after delivery date	
Best processing temperature: minimum 10 °C at least 8 hours before filling	
<p>* Hot filling: the packaging is suitable for hot filling, notably after hot filling the products can be more flexible. This can have influence on stacking, the packaging must be tested by the customer before approval for use.</p> <p>* Cold temperatures: Freezing conditions require special resins, available on request. The packaging must be tested by the customer before approval for use.</p>	

Miscellaneous

All deliveries are subject to the General Terms and Conditions of Sale of Intopack B.V. (Dutch chamber of commerce no. 16044140). Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that Intopack recommends. All Intopack Products comply with the European Union Commission Regulation No. 10/2011/EU with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. Deviations in the products of 0,025% or less (i.e. 25 items per 100.000) are considered acceptable in the industry and therefore cannot be construed as a defect. The product specification are subject to change without notice.

